



General Information

Technical Information

Tilttable	No
Technology	LED Integrated
Wattage	45W
Voltage (V)	220-240
Dimmable	Not Dimmable
Colour Code	830 Warm White
Colour temperature (Kelvin)	3000 Warm White
Colour Rendering (Ra)	80-89
Colour of Light	White
Light Colour Options	Single Color
Including bulb	Yes

Beam Angle (degree)	60
Luminous Flux (Lumen)	4725lm
Lumen per watt	105
Powerfactor	>0.90
Unified Glare Rating	< 19 - For offices
Optische Afdekking	PC (Polycarbonate)
Type product	LED Downlight

Fixture Information

Mounting Method	Surface
Cut out (mm)	250
IP-rating	IP65
Impact Protection (IK)	IK06 - 1 joule
Bedrijfstemperatuur	-20 to +40
Housing	Aluminium
Colour of the Fixture	White
Colour of material	White
Fixture Connection	Terminal, 3-Pole (L, N, PE)
Product Serie	DOWNLIGHT SURFACE IP65

Dimensions

Height (mm)	125
Diameter (mm)	250

Sensor Information  Guaranteed **budget prices**  Up to **7 years warranty**

Type of sensor  **Easy** return process  No Sensor  Long-life **LED solutions**