



## Specifications Noxion LED Panel Louvre Excell Pronox 38W 3850lm - 830 Warm White | 150x15cm - UGR 152 - Dali Dimmable

[View Product](#)

### General Information

|                      |                                                                    |
|----------------------|--------------------------------------------------------------------|
| SKU                  | 235768                                                             |
| EAN                  | 8719157006606                                                      |
| Manufacturer Code    | 8719157006606                                                      |
| Brand                | Noxion                                                             |
| Manufacturer Name    | Noxion LED Louvre Excell G2. 38W 3000K 1500 Matt DALI (1x49W eqv.) |
| Budgetlight warranty | 6 Years                                                            |
| Average Lifetime (h) | 70000                                                              |
| Product Serie        | Louvre Excell                                                      |

### Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Replaces (Watt)             | 1x49            |
| Wattage                     | 38W             |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Yes, Dali       |
| Colour Code                 | 830 Warm White  |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light Colour Options        | Single Color    |

|                        |                                         |
|------------------------|-----------------------------------------|
| Luminous Flux (Lumen)  | 3850lm                                  |
| Lumen per watt         | 101.3                                   |
| Suitable for Outdoor   | No                                      |
| IP-rating              | IP20                                    |
| Impact Protection (IK) | IK02 - 0.20 joule                       |
| Fixture Connection     | Terminal, 2-pole (MAINS)   2-pole (DIM) |
| Afwerking Reflector    | Frosted                                 |
| Inclusief Driver       | Yes                                     |
| Powerfactor            | >0.90                                   |
| Type product           | LED Panel                               |

## Fixture Information

|                       |                                  |
|-----------------------|----------------------------------|
| Mounting Method       | Recessed                         |
| Unified Glare Rating  | < 15 - For specific uses         |
| Optische Afdekking    | PET (Polyethylene Terephthalate) |
| Bedrijfstemperatuur   | -20 to +50                       |
| Emergency Lighting    | No                               |
| Colour of the Fixture | White                            |
| Housing               | Steel                            |
| Colour of material    | White                            |

## Dimensions

|                       |          |
|-----------------------|----------|
| Afmetingen LED Paneel | 150x15cm |
| Length (mm)           | 1495     |
| Width (mm)            | 150      |
| Height (mm)           | 55       |

## Sensor Information

Type of sensor

No Sensor

## Why Budgetlight?



Guaranteed **budget prices**



Up to **7 years warranty**



**Easy** return process



Long-life **LED solutions**

